

YTP 370 Flexo Machine

Model	YTP-F5-370	YTP-F5-460	YTP-F5-650
Max. Web Width	380mm	470mm	660mm
Max. Printing Width	370mm	460mm	650mm
Printing Unit	4 to 12	4 to 12	4 to 12
Substrate Thickness	0.02---0.50mm	0.02---0.50mm	0.02---0.50mm
Print Plate Thickness	1.14mm	1.14mm	1.14mm
Print Length	222.25-635mm	222.25-635mm	222.25-635mm
Printing Speed	5-200m/min	5-200m/min	5-200m/min
Unwind Roll Diameter Max.	800mm	800mm	800mm
Rewind Roll Diameter Max.	800mm	800mm	800mm
UV Dryer	LED UV/Mercury UV / Infrared Hot Air Drying LED UV/		

Main Features:

- The whole machine adopt dual Baumuller servo control system at each print deck, can realize online automatic registration, which guarantee high-precision printing.
- Print units are with classic petal structure to ensure simple and fast changeover. Each print station is equipped with chiller system, can effectively reduce the influence of high UV curing temperature, is ideal for the print of film and shrink material.
- Unwind and rewind system adopts automatic roll lifting mechanism to greatly improve roll changing efficiency.
- Optional setting includes movable cold foil and laminating device, delam relam, full rotary or intermittent die cutting, and plate mounting machine. Can add silk print, code spray, gravure print deck to combine with flexo printing.